

MATERIAL SAFETY DATA SHEET

MSDS Name: GRABBER ACOUSTIC SEALANT #GSCS  
Version Number 2  
MSDS Date: SEP-23-2003  
Page Number: 1

-----

SECTION I - PRODUCT AND COMPANY INFORMATION

Product Name: GRABBER ACOUSTIC SEALANT #GSCS  
HMIS Hazard Rating: Health: 1 Fire: 0 Reactivity: 0 PPE: B

Company name: JOHN WAGNER & ASSOC/GRABBER  
phone 925-687-6606  
205 MASON CIRCLE  
CONCORD  
CA 94520

Other Names: WATER BASED SOUND SEALANT

SECTION II - INGREDIENT AND HAZARD INFORMATION

Hazardous Ingredient Name	CAS Number	Percent	TSCA
ETHYLENE GLYCOL	107-21-1	< 2.0	Y
MINERAL SPIRITS	64742-48-9	< 2.0	Y

Ingredient Notes:  
Remaining ingredients are not considered OSHA hazardous.

-----

SECTION III - PHYSICAL AND CHEMICAL PROPERTIES

Form: Caulk  
Appearance/Color: WHITE  
Odor: Mild odor  
Solubility (in water): yes  
pH Value, +/- .3: 7.5  
Boiling Range: 212.°F (100.°C)  
Vapor Pressure (mmHg): 15.@ 68.°F (20.°C)  
Evaporation Rate: 0.6 times Slower than n-Butyl Acetate

Vapor Density: Heavier than air

% Volatile, Weight 15.%  
% Volatile, Volume 25.%  
Specific Gravity: 1.64  
VOC (less H2O or exempt) <25 gr/L (1%)

NOTE:

Odor : Mild acrylic odor. Freeze Point : 32 Deg F

-----

MATERIAL SAFETY DATA SHEET

MSDS Name: GRABBER ACOUSTIC SEALANT #GSCS  
Version Number 2  
MSDS Date: SEP-23-2003  
Page Number: 2

-----

-----  
**SECTION IV - FIRE FIGHTING MEASURES (Flash,UEL,LEL for solvent only)**

Flammability Class none  
Flash Range: Not Applicable  
Explosive Range (LEL/UEL): Not Applicable

**EXTINGUISHING MEDIA:**

Dry chemical -- Carbon Dioxide -- Foam -- Water Fog  
Will not burn in wet state.

**SPECIAL FIRE-FIGHTING PROCEDURES:**

Water may be used to cool and protect exposed containers.  
Caution should be taken because uncured material is water soluble.

**UNUSUAL FIRE AND EXPLOSION HAZARDS:**

Any closed container may burst when exposed to extreme heat or fire.

-----

**SECTION V - HEALTH HAZARD DATA**

**ROUTES OF ENTRY:**

ENTRY THROUGH...Inhalation and skin most likely

**CARCINOGENICITY...**

NTP? N/E | IARC Monographs? N/E | OSHA? NO

**EFFECTS OF OVEREXPOSURE**

Inhalation: May cause nose or throat irritation.  
Skin/Eye Contact: May cause irritation.  
Ingestion: Swallowing large amounts may cause nausea, vomiting. ( an unlikely route of entry )

**FIRST AID MEASURES**

Inhalation: If affected by inhalation, remove to fresh air.  
Eye Contact: Flush with water for at least 15 minutes, and get prompt medical attention.  
Skin Contact: Wash skin thoroughly with soap and water.  
Ingestion: Drink water, and get medical attention.

-----

N/A= Not applicable N/AV=Not available N/E, N/est=Not established

-----

**CHRONIC HAZARDS**

Swallowing ETHYLENE GLYCOL may cause gastrointestinal irritation.

-----

**SECTION VI - STABILITY AND REACTIVITY**

Stability: This product is stable  
Hazardous Polymerization: Hazardous polymerization will not occur

**INCOMPATABILITY:**

-----

MATERIAL SAFETY DATA SHEET

MSDS Name: GRABBER ACOUSTIC SEALANT #GSCS  
Version Number 2  
MSDS Date: SEP-23-2003  
Page Number: 3

None

CONDITIONS TO AVOID:

None

HAZARDOUS DECOMPOSITION PRODUCTS:

May produce oxides of carbon and oxides of nitrogen when burned.

SECTION VII - ACCIDENTAL RELEASE AND DISPOSAL MEASURES:

STEPS TO BE TAKEN IN CASE OF SPILL:

Wear appropriate protective clothing. Add dry absorbent and shovel or sweep up. Place in an appropriate container and seal.

WASTE DISPOSAL METHOD:

Dispose of in accordance with Federal, State, and Local regulations.

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

	ACGIH TLV	ACGIH TLV-C	ACGIH STEL	OSHA STEL	OSHA PEL
ETHYLENE GLYCOL	50.00 PPM	N/est	N/est	N/est	50.00 PPM
MINERAL SPIRITS	100.00 PPM	N/est	N/est	N/est	100.00 PPM

RESPIRATORY PROTECTION:

NIOSH respirators recommended if vapors and mists are generated.

VENTILATION:

Local exhaust is recommended for safe practice.

PROTECTIVE CLOTHING:

Gloves and clothing should be worn to prevent repeated skin contact.

EYE PROTECTION:

Splashproof goggles or safety glasses should be worn.

HANDLING AND STORAGE PRECAUTIONS:

Keep from freezing. Keep away from heat.

Keep containers closed when not in use.

Avoid prolonged or repeated contact with skin.

Keep out of the reach of children.

SECTION IX - TRANSPORT INFORMATION: (not all sizes available)

GROUND TRANSPORT (DOT) - DOMESTIC

Caulking compound, Non Regulated

AIR TRANSPORT (DOT) - DOMESTIC

Caulking compound, Non Regulated

MATERIAL SAFETY DATA SHEET

MSDS Name: GRABBER ACOUSTIC SEALANT #GSCS  
Version Number 2  
MSDS Date: SEP-23-2003  
Page Number: 4

---

**AIR TRANSPORT ( IATA ) - INTERNATIONAL**  
Caulking compound, Non Regulated

**MARINE - OCEAN TRANSPORT ( IMDG )**  
Caulking compound, Non Regulated

---

**SECTION X - REGULATORY INFORMATION:**

SARA TITLE III SECTION 313:

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right to Know Act of 1986 and of 40 CFR 372:

Ingredient Name	CAS Number	Percent
ETHYLENE GLYCOL	107-21-1	< 2.0

The following ingredients are registered for TSCA 12B

Ingredient Name	CAS Number	Percent
ETHYLENE GLYCOL	107-21-1	< 2.0

Ethylene Glycol fits the EPA Hazard Category definition of Immediate (Acute) and Delayed (Chronic) Health Hazards under SARA Sect.311,312. All chemical substances are TSCA listed.  
California PROP.65 Chemicals: none known

**DISCLAIMER:**

The information contained herein is based on data available as of the date of preparation of this MSDS and which we believe to be reliable. However, no warranty is expressed or implied regarding the accuracy of the data. We shall not be responsible for the use of this information, or of any product, method, apparatus mentioned, and user must make his own investigation to determine the suitability of the information or products for his particular purpose, for the protection of the environment, and the health & safety of the users of this material.